



PRODUCT DATA SHEET

ECONO BREAKER-TH100

Low Temperature Breaker Aid

DESCRIPTION

ECONO BREAKER-TH100 is an excellent breaker aid, and when used with **ECONO-PS1** or **ECONO-PS2** completes the degradation of guar and guar derivative based fracturing fluids at ambient temperatures. **ECONO BREAKER-TH100** is compatible with all stimulation additives and particularly, does not interfere with the activation mechanism of fracturing fluids.

PHYSICAL PROPERTIES:

Appearance:	Clear Light Yellow Liquid
Activity:	85%
Specific Gravity:	1.12
pH (neat):	10.5
Freeze Point	-10°F

RECOMMENDED USAGE:

Typical loadings of **ECONO BREAKER-TH100** range from 1.0-2.5 gal/1000 gallons of fluid along with 2-10lbs/1000 gallons of **ECONO-PS1** or **ECONO-PS2**. Usage may vary according to desired break time, temperature and other factors and pilot testing is strongly recommended.

PACKAGING

Shipped in 55.0 Gallon plastic drums and 264 & 317 Gallon plastic totes

DOT: Not Regulated

This information is provided with the best of our knowledge and belief. It is users responsibility to satisfy himself as to the suitability of such information for his own particular use. However, no representation, warranty or guarantee is made as to its accuracy, reliability. We do not accept liability for any loss or damage that may occur from the used of this information nor do we offer any warranty against any patent infringement.



P.O. Box 450246
Houston, TX 77245-0246
USA Toll free: (800) 231-2066
Phone: (713) 723-8416
Fax: (713) 723-1845
URL: www.EconomyPolymers.com
E-mail: economy@economypolymers.com