



PRODUCT DATA SHEET

ECOPOL-NE601

Non-Emulsifier

DESCRIPTION

Ecopol-NE601 is a highly effective nonionic non-emulsifier that prevents emulsions in both acid and fracturing fluids. **Ecopol-NE601** contains surfactants which deliver superior break times normally within 60 seconds even in the presence of crude oils with a high probability for sludge build-up.

PRODUCT ADVANTAGES

Ecopol-NE601 is designed to have excellent compatibility with a variety of acidizing or fracturing compounds such as corrosion inhibitors, iron control agents, anti-sludge agents, gelling agents and crosslinkers. **Ecopol-NE601** delivers superior wetting characteristics and a more efficient stimulation. **Ecopol-NE601** is designed to deliver a very low surface tension which aids in wettability and water recovery.

CHEMICAL & PHYSICAL PROPERTIES

| | |
|-------------------|--------------------|
| Appearance: | Pale Yellow Liquid |
| Specific Gravity: | 0.83 |
| Appearance/Odor: | Alcohol |
| Ionic Charge: | Non-Ionic |
| Pour Point: | less than -20°F |

TYPICAL USAGE

Ecopol-NE601 is designed for use when cationic or anionic products may not be desirable, yet **Ecopol-NE601** will not have a detrimental effect if used with a cationic or an anionic. **Ecopol-NE601** is designed to be formulated in hydrochloric acid or in a fracturing fluid at 0.5-2 gallons per 1000 gallons for non-emulsification purposes and offers a very cost effective and high quality alternative compared to other products.



P.O. Box 450246
Houston, TX 77245-0246
USA Toll free: (800) 231-2066
Phone: (713) 723-8416
Fax: (713) 723-1845
URL: www.EconomyPolymers.com
E-mail: economy@economypolymers.com



ECOPOL-NE601

SURFACE TENSION DATA @ 75°F

| | <u>0.5gpt</u> | <u>1.0gpt</u> | <u>2.0gpt</u> | <u>5.0gpt</u> |
|---------------------|----------------------|----------------------|----------------------|----------------------|
| Fresh Water | 33dyn/cm | 31dyn/cm | 30dyn/cm | 29dyn/cm |
| 2% KCl Water | 35dyn/cm | 32dyn/cm | 30dyn/cm | 29dyn/cm |

Please read and understand the Material Safety Data Sheet (MSDS) before using this product.

This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer any warranty against patent infringement.



P.O. Box 450246
Houston, TX 77245-0246
USA Toll free: (800) 231-2066
Phone: (713) 723-8416
Fax: (713) 723-1845
URL: www.EconomyPolymers.com
E-mail: economy@economypolymers.com