

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

### Product Identifier

**Product form:** Mixture

**Product name:** Ecopol-AA80

### Intended Use Of The Product

**Use of the substance/mixture:** Iron control agent

### Name, Address, And Telephone Of The Responsible Party

Economy® Polymers & Chemicals

435 E. Anderson Road

77047 Houston, TX

T 713-723-8416; 1-800-231-2066

[www.economypolymers.com](http://www.economypolymers.com)

### Emergency Telephone Number

**Emergency number** : CHEMTREC 1-800-424-9300 (US); 703-527-3887 (International, collect calls are accepted)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification Of The Substance Or Mixture

#### GHS-US classification

Flam. Liq. 2 H225

Acute Tox. 4 (Oral) H302

Acute Tox. 3 (Dermal) H311

Skin Corr. 1A H314

Eye Dam. 1 H318

STOT SE 1 H370

### Label Elements

#### GHS-US labeling

#### Hazard pictograms (GHS-US)



#### Signal word (GHS-US)

#### Hazard statements (GHS-US)

- : Danger
- : H225 - Highly flammable liquid and vapour.  
H302 - Harmful if swallowed.  
H311 - Toxic in contact with skin.  
H314 - Causes severe skin burns and eye damage.  
H318 - Causes serious eye damage.  
H370 - Causes damage to organs.
- : P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapors, mist, spray.  
P264 - Wash hands, forearms and other exposed areas thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P280 - Wear gloves, protective clothing, eye protection, face protection.  
P301+P312 - If swallowed, call a doctor if you feel unwell.

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 - Immediately call a POISON CENTER or doctor.  
P312 - Call a POISON CENTER or doctor if you feel unwell.  
P321 - Specific treatment (see section 4)  
P330 - If swallowed, rinse mouth.  
P361 - Remove/Take off immediately all contaminated clothing.  
P363 - Wash contaminated clothing before reuse  
P370+P378 - In case of fire: Use appropriate media for extinction  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up  
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

**Other Hazards** Not available

**Unknown acute toxicity (GHS US)** Not available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixture

Name	Product Identifier	% (w/w)	GHS-US classification
Acetic acid	(CAS No.) 64-19-7	80-90	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318
Methyl alcohol	(CAS No.) 67-56-1	10-20	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Full text of H-phrases: see section 16

### SECTION 4: FIRST AID MEASURES

#### Description Of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor/physician.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

#### Most Important Symptoms And Effects Both Acute and Delayed

**General:** Causes severe skin burns and eye damage. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed. Causes damage to organs. Harmful if swallowed.

**Inhalation:** Causes severe respiratory irritation if inhaled. Corrosive to the respiratory tract.

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Skin Contact:** Toxic in contact with skin. Causes severe irritation which will progress to chemical burns.

**Eye Contact:** Causes serious eye damage. Can cause blindness. Vapors may cause severe irritation and tearing.

**Ingestion:** Swallowing a small quantity of this material will result in serious health hazard. Fatal if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause blindness.

**Chronic symptoms:** May cause erosion of the teeth, inflammation of the nose and respiratory system, and darkening of the skin.

### **Indication Of Any Immediate Medical Attention And Special Treatment Needed**

If exposed or concerned, get medical advice and attention.

## **SECTION 5: FIREFIGHTING MEASURES**

### **Extinguishing Media**

**Suitable extinguishing media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water spray.

**Unsuitable extinguishing media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From The Substance Or Mixture**

**Fire hazard:** Highly flammable liquid and vapour

**Explosion hazard:** May form flammable/explosive vapour-air mixture.

**Reactivity:** Thermal decomposition generates :Corrosive vapours.

### **Advice For Firefighters**

**Firefighting instructions:** Exercise caution when fighting any chemical fire.

**Protection during firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>).May release flammable gases.Thermal decomposition generates :Corrosive vapours.

**Other information:** Do not allow the product to be released into the environment.

### **Reference To Other Sections**

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment And Emergency Procedures**

**General measures:** Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Do NOT breathe (vapor, mist, spray).

#### **For Non-Emergency Personnel**

**Protective equipment:** Use appropriate personal protection equipment (PPE).

**Emergency procedures:** Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective equipment:** Use appropriate personal protection equipment (PPE).

**Emergency procedures:** Ventilate area.

### **Environmental Precautions**

Prevent entry to sewers and public waters.

### **Methods And Material For Containment And Cleaning Up**

**For containment:** Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for cleaning up:** Clear up spills immediately and dispose of waste safely.

### **Reference To Other Sections**

See heading 8, exposure controls and personal protection.

## **SECTION 7: HANDLING AND STORAGE**

### **Precautions For Safe Handling**

**Additional hazards when processed:** Handle empty containers with care because residual vapours are flammable.

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Hygiene measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Wash hands, forearms, and other exposed areas thoroughly after handling.

### **Conditions For Safe Storage, Including Any Incompatibilities**

**Technical measures:** Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Comply with applicable regulations.

**Storage conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Protect from freezing

**Incompatible materials:** Strong acids. Strong bases. Strong oxidizers. Heat sources.

**Storage area:** Store locked up. Store in a well-ventilated place. Keep cool

### **Specific End Use(s)**

Iron control agent

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Control Parameters**

<b>Acetic acid (64-19-7)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	10 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	37 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	15 ppm
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	10 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	37 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	15 ppm
USA IDLH	US IDLH (ppm)	50 ppm
Alberta	OEL STEL (mg/m <sup>3</sup> )	37 mg/m <sup>3</sup>
Alberta	OEL STEL (ppm)	15 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	10 ppm
British Columbia	OEL STEL (ppm)	15 ppm
British Columbia	OEL TWA (ppm)	10 ppm
Manitoba	OEL STEL (ppm)	15 ppm
Manitoba	OEL TWA (ppm)	10 ppm
New Brunswick	OEL STEL (mg/m <sup>3</sup> )	37 mg/m <sup>3</sup>
New Brunswick	OEL STEL (ppm)	15 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	10 ppm
Newfoundland & Labrador	OEL STEL (ppm)	15 ppm
Newfoundland & Labrador	OEL TWA (ppm)	10 ppm
Nova Scotia	OEL STEL (ppm)	15 ppm
Nova Scotia	OEL TWA (ppm)	10 ppm
Nunavut	OEL STEL (mg/m <sup>3</sup> )	39 mg/m <sup>3</sup>
Nunavut	OEL STEL (ppm)	15 ppm
Nunavut	OEL TWA (mg/m <sup>3</sup> )	26 mg/m <sup>3</sup>
Nunavut	OEL TWA (ppm)	10 ppm

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	39 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (ppm)	15 ppm
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	26 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (ppm)	10 ppm
Ontario	OEL STEL (ppm)	15 ppm
Ontario	OEL TWA (ppm)	10 ppm
Prince Edward Island	OEL STEL (ppm)	15 ppm
Prince Edward Island	OEL TWA (ppm)	10 ppm
Québec	VECD (mg/m <sup>3</sup> )	37 mg/m <sup>3</sup>
Québec	VECD (ppm)	15 ppm
Québec	VEMP (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup>
Québec	VEMP (ppm)	10 ppm
Saskatchewan	OEL STEL (ppm)	15 ppm
Saskatchewan	OEL TWA (ppm)	10 ppm
Yukon	OEL STEL (mg/m <sup>3</sup> )	43 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	25 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	10 ppm

### Methyl alcohol (67-56-1)

Mexico	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	200 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	310 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	250 ppm
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	325 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA IDLH	US IDLH (ppm)	6000 ppm
Alberta	OEL STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
Alberta	OEL STEL (ppm)	250 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	250 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	250 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
New Brunswick	OEL STEL (ppm)	250 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	200 ppm

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

New Foundland & Labrador	OEL STEL (ppm)	250 ppm
New Foundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	250 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
Nunavut	OEL STEL (ppm)	250 ppm
Nunavut	OEL TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
Nunavut	OEL TWA (ppm)	200 ppm
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (ppm)	250 ppm
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (ppm)	200 ppm
Ontario	OEL STEL (ppm)	250 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	250 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
Québec	VECD (ppm)	250 ppm
Québec	VEMP (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
Québec	VEMP (ppm)	200 ppm
Saskatchewan	OEL STEL (ppm)	250 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m <sup>3</sup> )	310 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	250 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	200 ppm

### Exposure Controls

**Appropriate engineering controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapours may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Provide sufficient ventilation to keep ammonia vapors below the permissible exposure limit.

**Personal protective equipment:** Gloves. Protective clothing. Face shield. Head/neck protection. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for protective clothing:** Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing. Corrosionproof clothing

**Hand protection:** Wear chemically resistant protective gloves.

**Eye protection:** Chemical goggles or safety glasses. Chemical goggles or face shield.

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Skin and body protection:** Wear suitable protective clothing.

**Respiratory protection:** Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

**Thermal hazard protection:** Wear suitable protective clothing.

**Other information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information On Basic Physical And Chemical Properties

Physical state	: Liquid
Appearance	: Clear,orange,Transparent
Odour	: Not available
Odour threshold	: Not available
pH	: 2 - 4
Relative evaporation rate (butylacetate=1)	: Not available
Melting point	: -25 °C (-13°F)
Freezing point	: Not available
Boiling point	: 65 °C (149°F)
Flash point	: 12 °C (53.6°F)
Auto-ignition temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower flammable limit	: Not available
Upper flammable limit	: Not available
Vapour pressure	: Not available
Relative vapour density at 20 °C	: Not available
Relative density	: Not available
Specific gravity	: 0.98-1.01
Solubility	: Not available
Log Pow	: Not available
Log Kow	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: Not available
Explosion data - sensitivity to mechanical impact	: Not available
Explosion data - sensitivity to static discharge	: Not available

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity** Thermal decomposition generates :Corrosive vapours.

**Chemical Stability** Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

**Possibility Of Hazardous Reactions** Hazardous polymerization will not occur.

**Conditions To Avoid** Direct sunlight. Extremely high or low temperatures. Open flame. Sparks.

**Incompatible Materials** Strong acids. Strong bases. Strong oxidizers.

**Hazardous Decomposition Products** Carbon oxides (CO, CO<sub>2</sub>). May release flammable gases. Thermal decomposition generates :Corrosive vapours.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information On Toxicological Effects - Product

**Acute toxicity** : Harmful if swallowed. Toxic in contact with skin.

**LD50 and LC50 Data** Not available

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Skin corrosion/irritation:** Causes severe skin burns and eye damage. **pH:** 2 - 4

**Serious eye damage/irritation:** Causes serious eye damage. **pH:** 2 - 4

**Respiratory or skin sensitisation:** Not classified

**Germ cell mutagenicity:** Not classified

**Teratogenicity:** Not available

**Carcinogenicity:** Not classified

**Specific target organ toxicity (repeated exposure):** Not classified

**Reproductive toxicity:** Not classified

**Specific target organ toxicity (single exposure):** Causes damage to organs.

**Aspiration hazard:** Not classified

**Potential Adverse human health effects and symptoms:** Toxic in contact with skin. Harmful if swallowed.

**Symptoms/injuries after inhalation:** Causes severe respiratory irritation if inhaled. Corrosive to the respiratory tract.

**Symptoms/injuries after skin contact:** Toxic in contact with skin. Causes severe irritation which will progress to chemical burns.

**Symptoms/injuries after eye contact:** Causes serious eye damage. Can cause blindness. Vapors may cause severe irritation and tearing.

**Symptoms/injuries after ingestion:** Swallowing a small quantity of this material will result in serious health hazard. Fatal if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic symptoms:** May cause erosion of the teeth, inflammation of the nose and respiratory system, and darkening of the skin.

### Information On Toxicological Effects - Ingredient(s)

#### **LD50 and LC50 Data**

<b>Acetic acid (64-19-7)</b>	
LD50 oral rat	3310 mg/kg
LD50 dermal rabbit	1060 mg/kg
LC50 inhalation rat (mg/l)	11.4 mg/l (Exposure time: 4 h)

  

<b>Methyl alcohol (67-56-1)</b>	
LC50 inhalation rat (mg/l)	83.2 mg/l (Exposure time: 4 h)
ATE (oral)	100 mg/kg
ATE (dermal)	300 mg/kg
ATE (vapours)	3 mg/l/4h

## **SECTION 12: ECOLOGICAL INFORMATION**

### **Toxicity**

<b>Acetic acid (64-19-7)</b>	
LC50 fishes 1	79 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	47 mg/l (Exposure time: 24 h - Species: Daphnia magna)
LC50 fish 2	75 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	65 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

  

<b>Methyl alcohol (67-56-1)</b>	
LC50 fishes 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

### **Persistence And Degradability**

<b>Ecopol-AA80</b>	
Persistence and degradability	Not established.

### **Bioaccumulative Potential**

<b>Ecopol-AA80</b>	
Bioaccumulative potential	Not established.



# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetic acid (64-19-7)	
Log Pow	-0.31 (at 20 °C)
Methyl alcohol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77

**Mobility In Soil** Not available

### Other Adverse Effects

**Other information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste disposal recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Additional information:** Handle empty containers with care because residual vapours are flammable.

**Ecology - waste materials:** Hazardous waste due to toxicity.

## SECTION 14: TRANSPORT INFORMATION

In accordance with ICAO/IATA/DOT/TDG

### UN Number

UN-No.(DOT): 2920

DOT NA no.: UN2920

### UN Proper Shipping Name

**DOT Proper Shipping Name** : Corrosive liquids, flammable, n.o.s. (Acetic acid, methyl alcohol)

**Department of Transportation (DOT) Hazard Classes** : 8 - Class 8 - Corrosive material 49 CFR 173.136

**Hazard labels (DOT)** : 8 - Corrosive substances

3 - Flammable liquid



### DOT Symbols

: G - Identifies PSN requiring a technical name

### Packing group (DOT)

: I - Great Danger

### DOT Special Provisions (49 CFR 172.102)

: A6 - For combination packagings, if plastic inner packagings are used, they must be packed in tightly closed metal receptacles before packing in outer packagings.

B10 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks, and DOT 57 portable tanks are not authorized.

T14 - 6 mm Prohibited 178.275(g)(3).

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the formula: Where:  $t_r$  is the maximum mean bulk temperature during transport,  $t_f$  is the temperature in degrees celsius of the liquid during filling, and  $\alpha$  is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling ( $t_f$ ) and the maximum mean bulk temperature during transportation ( $t_r$ ) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: Where:  $d_{15}$  and  $d_{50}$  are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

**DOT Packaging Exceptions (49 CFR 173.xxx)** : None

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**DOT Packaging Non Bulk (49 CFR 173.xxx)** : 201

**DOT Packaging Bulk (49 CFR 173.xxx)** : 243

### Additional information

**Emergency Response Guide (ERG) Number** : 132

**Overland transport** Not available

### Transport by sea

**DOT Vessel Stowage Location** : C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel.

**DOT Vessel Stowage Other** : 25 - Shade from radiant heat, 40 - Stow "clear of living quarters"

### Air transport

**DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)** : 0.5 L

**DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)** : 2.5 L

## SECTION 15: REGULATORY INFORMATION

### US Federal regulations

#### **Acetic acid (64-19-7)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### **Methyl alcohol (67-56-1)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

**SARA Section 313 - Emission Reporting** 1.0 %

### US State regulations

#### **Methyl alcohol (67-56-1)**

**U.S. - California - Proposition 65 - Developmental Toxicity** WARNING: This product contains chemicals known to the State of California to cause birth defects.

#### **Acetic acid (64-19-7)**

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities  
U.S. - Hawaii - Occupational Exposure Limits - STELs  
U.S. - Hawaii - Occupational Exposure Limits - TWAs  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
U.S. - Louisiana - Reportable Quantity List for Pollutants  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Right To Know List  
U.S. - Massachusetts - Toxics Use Reduction Act  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Michigan - Polluting Materials List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances  
U.S. - North Carolina - Control of Toxic Air Pollutants  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater  
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

### **Methyl alcohol (67-56-1)**

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute  
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic  
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)  
U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Connecticut - Volatile Substances  
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities  
U.S. - Hawaii - Occupational Exposure Limits - Skin Designations  
U.S. - Hawaii - Occupational Exposure Limits - STELs  
U.S. - Hawaii - Occupational Exposure Limits - TWAs  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
U.S. - Illinois - Toxic Air Contaminants  
U.S. - Louisiana - Reportable Quantity List for Pollutants  
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants  
U.S. - Maine - Chemicals of High Concern  
U.S. - Massachusetts - Allowable Ambient Limits (AALs)  
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Right To Know List  
U.S. - Massachusetts - Threshold Effects Exposure Limits (TEELs)  
U.S. - Massachusetts - Toxics Use Reduction Act  
U.S. - Michigan - Occupational Exposure Limits - Skin Designations  
U.S. - Michigan - Occupational Exposure Limits - STELs  
U.S. - Michigan - Occupational Exposure Limits - TWAs

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Michigan - Polluting Materials List  
U.S. - Minnesota - Groundwater Health Risk Limits  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - Skin Designations  
U.S. - Minnesota - Permissible Exposure Limits - STELs  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
U.S. - New Jersey - Environmental Hazardous Substances List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria  
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual  
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations  
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories  
U.S. - Tennessee - Occupational Exposure Limits - Skin Designations  
U.S. - Tennessee - Occupational Exposure Limits - STELs  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - Skin Designations  
U.S. - Vermont - Permissible Exposure Limits - STELs  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List  
U.S. - Washington - Permissible Exposure Limits - Skin Designations  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs

### Canadian regulations

#### Ecopol-AA80

WHMIS Classification

Class B Division 2 - Flammable Liquid  
Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects  
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects



#### Acetic acid (64-19-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification

Class B Division 3 - Combustible Liquid

# Ecopol-AA80

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Methyl alcohol (67-56-1)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

### SECTION 16: OTHER INFORMATION

**Indication of changes**

: Revision date: 08/19/2013

**Other information**

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**GHS Full Text Phrases:**

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Corr. 1A	skin corrosion/irritation Category 1A
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H370	Causes damage to organs

**Party Responsible For The Preparation Of This Document:**

Economy Polymers & Chemicals  
435 E. Anderson Road Houston, TX 77047  
713-723-8416; 1-800-231-2066

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS