



EcoThick LB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 10/5/2016

Version: 1.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Identifier

Product Form: Mixtures

Product Name: EcoThick LB

Synonyms: Emulsion Polymer

Intended Use of the Product

Use of the Substance/Mixture: Gelling Agent/Friction Reducer

For professional use only

Name, Address, and Telephone of the Responsible Party

Economy® Polymers & Chemicals

435 E. Anderson Road

77047 Houston, TX

T 1-800-231-2066

www.economypolymers.com

Emergency Telephone Number

Emergency number : CHEMTREC 1-800-424-9300 (US); 703-527-3887 (International, collect calls are accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315

Eye Irrit. 2A H319

STOT SE 3 H336

Asp. Tox. 1 H304

Aquatic Acute 2 H401

Aquatic Chronic 2 H411

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

- : H304 - May be fatal if swallowed and enters airways
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H336 - May cause drowsiness or dizziness
- H401 - Toxic to aquatic life
- H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

- : P261 - Avoid breathing vapors, mist, spray.
- P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves, protective clothing, eye protection, face protection, respiratory protection.
- P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

EcoThick LB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER or doctor if you feel unwell
P321 - Specific treatment (see section 4).
P331 - If swallowed, do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362 - Take off contaminated clothing.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: None

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	15 – 40	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
2-Propenoic acid, polymer with 2-propenamamide, sodium salt	(CAS No) 25987-30-8	10 - 30	Comb. Dust Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Most Important Symptoms and Effects Both Acute and Delayed

General: Eye irritation. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Vapors may cause drowsiness and dizziness.

Inhalation: May cause drowsiness or dizziness

Skin Contact: Causes skin irritation

Eye Contact: Causes serious eye irritation

EcoThick LB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ingestion: May be fatal if swallowed and enters airways

Chronic Symptoms: Not available

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam, dry chemical

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive

Reactivity: Upon thermal decomposition nitrogen oxides and acrid fumes may be released

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Acrid vapors. Nitrogen oxides. Hydrocarbons. Carbon oxides (CO, CO₂). Toxic fumes are released.

Other information: Do not allow run-off from fire fighting to enter drains or water courses

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (vapors, mist, spray). Use only outdoors or in a well-ventilated area. Handle in accordance with good industrial hygiene and safety practice. Do not allow product to spread into the environment. Do not get in eyes, on skin, or on clothing

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection. Use appropriate personal protection equipment (PPE).

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Collect spillage. Absorb and/or contain spill with inert material, then place in suitable container. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Upon thermal decomposition nitrogen oxides and acrid fumes may be released. Do not pressurize, cut, or weld containers. When heated to decomposition, emits toxic fumes.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash hands and forearms thoroughly after handling. Do not eat, drink or smoke when using this product.

EcoThick LB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store in a well-ventilated place. Keep container tightly closed. Keep/Store away from extremely high or low temperatures, direct sunlight, ignition sources, incompatible materials.

Incompatible Materials: Strong acids, Strong bases, Strong oxidizers, Direct sunlight, Air, Oxidizer

Storage Area: Store locked up

Specific End Use(s)

Friction Reducer. For professional use only

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Petroleum distillates, hydrotreated light (64742-47-8)

British Columbia	OEL TWA (mg/m ³)	200 mg/m ³ (application restricted to conditions in which there are negligible aerosol exposures)
------------------	------------------------------	--

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed

Personal Protective Equipment: Gloves. Protective goggles. Insufficient ventilation: wear respiratory protection. Protective clothing



Materials for Protective Clothing: Chemically resistant materials and fabrics

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Milky, white, opaque, liquid
Odor	: Mild, hydrocarbon
Odor Threshold	: Not available
pH	: 6 - 9
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: -15 °C (5°F)
Freezing Point	: Not available
Boiling Point	: > 100 °C (>212°F)
Flash Point	: > 100 °C (>212°F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available

EcoThick LB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.03-1.06
Solubility	: Soluble in water
Log Pow	: Not available
Log Kow	: Not available
Viscosity, Kinematic	: Not available
Viscosity, Dynamic	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not available
Explosion Data – Sensitivity to Static Discharge	: Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Upon thermal decomposition nitrogen oxides and acrid fumes may be released

Chemical Stability: Stable at standard temperature and pressure.

Possibility of Hazardous Reactions: Upon thermal decomposition nitrogen oxides and acrid fumes may be released **Conditions to Avoid:** Extremely high or low temperatures. Sources of ignition. Incompatible materials. Direct sunlight. **Incompatible**

Materials: Strong acids, strong bases, strong oxidizers. Direct sunlight. Air, Oxidiser.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Hydrocarbons. Acrid vapors. Nitrogen oxides. Toxic gases.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity : Not classified

LD50 and LC50 Data Not available

Skin Corrosion/Irritation: Causes skin irritation.pH: 6 - 9

Serious Eye Damage/Irritation: Causes serious eye irritation. pH: 6 - 9

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: May cause drowsiness or dizziness.

Symptoms/Injuries After Skin Contact: Causes skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: May be fatal if swallowed and enters airways.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat (mg/l)	> 5.2 mg/l/4h

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Toxic to aquatic life with long lasting effects.

EcoThick LB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	4720 mg/l (Exposure time: 96 h - Species: Den-dronereides heteropoda)
LC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Persistence and Degradability

EcoThick LB	
Persistence and Degradability	May cause long-term adverse effects in the environment.

Bioaccumulative Potential

EcoThick LB	
Bioaccumulative Potential	Not established.

Petroleum distillates, hydrotreated light (64742-47-8)	
BCF fish 1	61 - 159

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

UN Number Not regulated for transport

UN Proper Shipping Name Not regulated for transport

Additional Information Not regulated for transport

Transport by sea Not regulated for transport

Air transport Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

EcoThick LB	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

2-Propenoic acid, polymer with 2-propenamide, sodium salt (25987-30-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

Petroleum distillates, hydrotreated light (64742-47-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

US State Regulations

2-Propenoic acid, polymer with 2-propenamide, sodium salt (25987-30-8)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	

Petroleum distillates, hydrotreated light (64742-47-8)	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	


Canadian Regulations

EcoThick LB	
--------------------	--

EcoThick LB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
	

2-Propenoic acid, polymer with 2-propenamide, sodium salt (25987-30-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION

Indication of Changes

: Revision date 10/5/2016

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H232	May form combustible dust concentrations in air
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness

EcoThick LB

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects

Party Responsible for the Preparation of This Document

Economy Polymers & Chemicals

435 E. Anderson Road Houston, TX 77047

1-800-231-2066

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

North America GHS US 2012 & WHMIS