



PRODUCT DATA SHEET

ECOPOL BREAKER-MGX

LIQUID BREAKER FOR GELLED OIL SYSTEMS

ECOPOL BREAKER-MGX is a liquid breaker for application in gelled oil systems.

PHYSICAL PROPERTIES

Specific Gravity	1.08
Solubility in Water	Soluble
Appearance	Opaque white liquid
Flash Point	151°F
pH (5% solution)	10-10.5
Activity	22%

PRODUCT FEATURES

- Effective easy to feed liquid formulation
- Compatible with other Economy gelled oil system products.
- Environmentally Friendly Formulation
- Low freezing point for cold weather application (<-20°F)

PRODUCT APPLICATION

ECOPOL BREAKER-MGX is typically used in the amounts of 5-10 gal/1000gal or higher, but further testing is strongly recommended as temperature, gel loading, and other testing conditions will have an impact on the amount of breaker needed.

PACKAGING

ECOPOL BREAKER is available in poly totes (264, 317 gallon) and bulk

TRANSPORTATION REGULATIONS

DOT Shipping Name: NA 1993, Combustible Liquid, n.o.s., 3, III

This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer any warranty against patent infringement.