



PRODUCT DATA SHEET

ECOPOL-FR2

BIODEGRADABLE FRICTION REDUCER ADDITIVE

GENERAL INFORMATION

ECOPOL-FR2 is a high molecular weight, biodegradable friction reducer. This product is designed to enhance the water displacement in oil wells by considerably reducing the friction pressure experienced at very high flow rates.

ADVANTAGES

ECOPOL-FR2 is designed to perform similarly to other friction reducer additives, but with a biodegradable active ingredient. **ECOPOL-FR2** performs more efficiently than most acrylamide based polymers at high salt concentrations and also can be broken with conventional fracturing fluid breakers (oxidizers, enzymes, etc.).

PROPERTIES

Appearance Beige Color Slurry Specific Gravity 1.05

FEEDING AND DOSAGE

Recommended use levels are 0.25%-1.0gal/1000gal in water. This product should not be used neat. Use positive displacement pumps (gear or progressive cavity).

STORAGE

Keep container sealed and away from moisture.

PACKAGING

ECOPOL-FR2 is available in 264 gallon totes, 317 gallon totes, or bulk.

This information is provided with the best of our knowledge and belief. It is user's responsibility to satisfy himself as to the suitability of such information for his own particular use. However, no representation, warranty or guarantee is made as to its accuracy, reliability. We do not accept liability for any loss or damage that may occur from the used of this information nor do we offer any warranty against any patent infringement.



P.O. Box 450246 Houston, TX 77245-0246 USA Toll free: (800) 231-2066 Phone: (713) 723-8416

Fax: (713) 723-1845

URL: www.EconomyPolymers.com E-mail: economy@economypolymers.com